



COVERING WHITE LABELS

Technical data sheet

FACE MATERIAL:

Description: A matt, white woodfree machine finished paper with blue backcoating, providing good opacity, excellent absorption and superior toner bonding characteristics. Facestock is made with FSC pulp

Use: Applications are labels where high opacity is important such as office labels for error correction or to cover up obsolete information

TECHNICAL DATA	Grammage	Caliper
	70 g/ M2	0,080 micron
	ISO 536	ISO 534

ADHESIVE:

Description: A general purpose permanent, acrylic based adhesive.

Performances The adhesive is characterized by a high initial tack, excellent adhesion and good low temperature performances on a wide variety of substrates.

Shelf life: 2 years, stored at 22 C° and 50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	700N/ m	0	- 20	+ 80

BACKING PAPER:

Description: A one side coated, bleached kraft paper

Application: This product is designed for the manufacture of A4 sheets for use in laser printers, copiers and monochrome inkjet printers.

TECHNICAL DATA	Grammage	Caliper
	g/m2	mm
	57	0,057

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.