



DEEP FREEZE LABELS

Technical data sheet

FACE MATERIAL:

Description: A matt, white woodfree, machine finished paper.
Use: The products is ideal for abel applications using variable information such as address, instruction and inventory labels, labels for office use and many other applications.

TECHNICAL DATA	Grammage	Caliper
	68 g/ M2	79 micron
	ISO 536	ISO 534

ADHESIVE:

Description: A general purpose permanent, rubber based adhesive.
Performances Excellent tack and adhesion to most surfaces, including apolar materails such as polyethylene. Even on slightly damp surfaces, the adhesive often performs well.

TECHNICAL DATA	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	° C	° C	° C
	-5	-40	+ 80

BACKING PAPER:

Description: A white one side clay coated, bleached kraft paper.
Application: The product is designed for the manufacture of continuous form products for use I high speed laser printers and impact printers. The construction provides good fanfolding and refolding properties.

TECHNICAL DATA	Grammage	Caliper
	g/m2	mm
	75	77

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.