



WHITE POLYESTER MATT LABELS

Technical data sheet

FACE MATERIAL:

Description: White. heat stabilised, matt coated computer imprintable polyester film.
Use: Information labelling where overprinting is made by laser or thermal transfer. Recommended for drum and logistics labelling

TECHNICAL DATA	Grammage	Caliper
	75 g/ M2	58 Micron

ADHESIVE:

Description: Acrylic water bone clear permanent adhesive
Performances Designed for filmic face materials. Excellent clarity, UV-stability and good water resistance once labelled. Good adhesion properties and heat resistance.
Limitations: Limited adhesion at low temperatures
Shelf life: From the date of manufacture 2 years in + 20C° and RH 50%

TECHNICAL DATA	Tack (min)	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	9 N	5	- 20	+ 100

BACKING PAPER:

Description: Matt coated kraft backing paper
Application: A4 applications for laser end-use

TECHNICAL DATA	Substance	Caliper	Opacity
	g/m2	micron	%
	100	88	89

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.