



VOID SILVER MATT LABELS

Technical data sheet

FACE MATERIAL:

Description: Imprintable matt silver polyester film, with a special absorbent surface coating, "void" printed

Use: Once applied to the substrate on removal, an irreversible "void" footprint message will detach itself from the face film. Labels which have been removed cannot be reapplied since repositioning will leave visible proof that tampering has taken place. The top coated of this facestock allows all the conventional printing as well as thermal transfert, dot, matrix laser etc.

Note. Preliminary tests have to be done on the substrate in real condition of use

TECHNICAL DATA	Grammage	Caliper
	82 g/ M2	60 microns

ADHESIVE:

Description: Permanent adhesive/acrylic based

Performances Adhesive perfectly adapted for uses that need very high label transparence. Very strong final adhesion on a wide range of substrates.

Shelf life. 2 years at 22 °C and 50 % HR

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	560 N	+ 5	- 40	+ 90

BACKING PAPER:

Description: A one side coated, bleached kraft

Application: The relatively low moisture sensitivity of this backing paper provides stable products under varying conditions. Suitable for fanfold and toll-to-sheet conversion, and all requiring good body and layflatness

TECHNICAL DATA	Substance	Caliper
	g/m2	mm
	99	100

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.