



## COATED PAPER

### Technical data sheet

#### FACE MATERIAL:

**Description:** Machine coated paper for high quality labels.  
**Use:** Ideal for multicolour prints requiring exceptional contrast and great details.

<b>TECHNICAL DATA</b>	Grammage	Caliper	Brightness	Opacity
	80 g/ M2	65 Micron	95 %	88 %

#### ADHESIVE:

**Description:** Modified acrylic adhesive in water emulsion  
**Performances:** Special adhesive designed for the production of "all -temperature" pressure sensitive adhesive for paper labels which require a broad service temperature range from -20 °C up to +80°C  
**Shelf life:** 2 years, stored at 22 C° and 50% RH

<b>TECHNICAL DATA</b>	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N- FTM 9	° C	° C	° C
	1600N/m	+ 5	- 20	+ 80

#### BACKING PAPER:

**Description:** Super calendered glassine paper, siliconised on one side  
**Application:** Backing paper designed for automatic label generation. Ideal for photocells dispensing system.

<b>TECHNICAL DATA</b>	Substance	Caliper
	g/m2	micron
	60	54

Our recommendations are based on our experience and up-to-date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all earlier ones. All information could be changed without notice.