



## ECO THERMAL PAPER FOR BALANCE

### Technical data sheet

#### FACE MATERIAL:

<b>Description</b>	White thermal paper without protective surface coat
<b>Use</b>	Non top-coated thermal paper featuring high sensitivity, designed for bar-code labels. Suitable for industrial sectors where no particular resistance to external agents ( humidity, oils, solvents, etc... ) is required.

<b>TECHNICAL DATA</b>	Weight	Caliper
	74 g/m2	80 Micron

#### ADHESIVE:

<b>Description</b>	Permanent, acrylic based adhesive
<b>Performances</b>	It's a universally applicable permanent adhesive.
<b>Shelf life</b>	2 years, stored at 22° and 45% RH

<b>TECHNICAL DATA</b>	Tack (min)	Application Temperature (min)	Service Temperature (min)
	°C	°C	°C
	0	-30	+80

#### BACKING PAPER:

<b>Description</b>	Honey, supercalendered glassine
<b>Application</b>	This supercalendered glassine is perfectly suited for assignment in labelling machines equipped with optical or mechanical scanners.

<b>TECHNICAL DATA</b>	Substance	Caliper	Transparency
	g/m2	micron	%
	50	45	52

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.