



MULTIPURPOSE LABEL _ ENVELOPE

Technical data sheet

FACE MATERIAL:

- Description** White, machine –finished label paper
- Use** The material is equally suitable for thermo transfer printing and is thus universally applicable. The paper complies with BfR XXXVI recommendations for direct contact with dry and /or greasy food.

TECHNICAL DATA	Weight	Caliper	Opacity
	g/m2	Microns	%
	72	68	83

ADHESIVE:

- Description** A permanent, acrylic based adhesive
- Performances** It's a universally applicable permanent adhesive. Its wide range of applications include price marking, computer labels and high quality industrial labels. It is suited for labelling rough but not extremely curved surfaces and is highly resistant to light, heat and ageing
- Shelf life** 4 years

TECHNICAL DATA	Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
		°C	°C	°C
	High	0	-30	+80

BACKING PAPER:

- Description** Honey, supercalendered glassine
- Application** The glassine is perfectly suited for assignment in labelling machines equipped with optical or mechanical scanners.

TECHNICAL DATA	Weight	Caliper	Transparency
	g/m2	Microns	%
	59	52	54

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.